



THE SPEC LINE
WHAT THE JOB DEMANDS.®

711

Self Adhering Flashing Tape

Meets or Exceeds AAMA 711 Specification

WHAT'S YOUR JOB?

- WINDOWS
- DOORS

THE SPECIFICATION

Meets or exceeds AAMA 711 Voluntary Specification for Self Adhered Flashing Used for Installation of Exterior Wall Fenestration Products.

THE PRODUCT

DAP® LT Poly Flash 711 Flashing Tape is a self-adhered waterproofing membrane designed to protect windows, doors, and thru-wall penetrations from moisture infiltration. The block copolymer adhesive allows for application in temperatures as low as 0° F, on OSB, plywood, aluminum, vinyl, and weather resistive barriers. The split release liner makes installation easier.

- Convenient 30' Roll
- Split Release Liner
- Can be applied in low temperatures to 0°F
- Can be applied to damp surfaces
- Seals around fasteners





THE SPEC LINE
WHAT THE JOB DEMANDS.®

711

Self Adhering Flashing Tape

Meets or Exceeds AAMA 711 Specification

LIMITED WARRANTY

DAP Products Inc. warrants that this product, when applied in accordance with DAP's label, technical bulletins and applicable industry standards, will be free from defects in material for 12 months from the date of purchase. Since methods of application and on-site conditions are beyond DAP's control and could affect performance, DAP makes no other warranties, express or implied, including the warranties of Merchantability or Fitness for a Particular Use or Purpose. If a product defect is encountered, call 1-888-DAP-TIPS for warranty fulfillment. You must have your sales receipt and product container available when you call. DAP's sole liability is either to supply replacement product or refund the purchase price. DAP will in no event be liable for incidental or consequential damages.

QUESTIONS?

Call 1-888-DAP-TIPS or visit dap.com and click on "Ask the Expert".

Performance Facts

Coverage: 4" x 30' (10 ft²)

Recommended Use: For installing fenestration products as part of the building envelope.

Features: Split release liner for easy installation • Seals nail penetrations • Low temperature application • Adheres to damp surfaces

Adheres To: OSB, Plywood, integral and nonintegral weather resistive barriers, masonry, vinyl, aluminum and most common building materials

SPECIFICATIONS:

AAMA 711-13 Meets or Exceeds
Complies With: ASTM E2112 sec. 5.13 and AAMA 2400

PHYSICAL PROPERTIES:

Solids: 100%
Application Range: 0°F to 225°F
Service Temperature: -40°F to 150°F
Shelf Life: 18 months
Adhesive Thickness: 7 mil
Staining: None

Part Number	Product Description	Size	Unit UPC	Case UPC Code (SCC14)	Case Pack/ Pallet Qty	Case Weight Lbs.	Case Dimensions (LxWxH)
7079880827	DAP LT POLY FLASH TAPE	4"x30'	070798808270	10070798808277	12/48	15	9" x 9" x 12.5"