

DYNAFLEX® 800

SUBMITTAL



**ON THE JOB
SINCE 1865**



JOB REFERENCE	JOB NAME	JOB LOCATION

SUBMITTED TO		SUBMITTED BY	
DATE	PHONE	DATE	PHONE

APPLICATION	PRODUCT SPECIFICATIONS
As a window installation sealant for use behind the flanges or mounting fins in wood frame construction.	Meets AAMA 800 (803 & 804 Specification voluntary specifications and test methods for sealants) AAMA – Verified Component List

DESCRIPTION	PERFORMANCE FACTS
<p>DAP® DYNAFLEX® 800 Premium Polymer Sealant provides a watertight, weatherproof seal. Can be used to install & seal around windows, doors & penetrations where a tough durable seal is required. Ideal for sealing dissimilar substrates & has excellent adhesion to most common building materials.</p>	<p>Amount per Cartridge: 300 ml (10.1 fl. oz.) Recommended Bead: 1/4" to 3/8" Coverage per Cartridge: 1/4" bead, 31 lin. ft. • 3/8" bead, 14 lin. ft.</p> <p>Recommended Use: Interior & exterior window & door installation & weatherization sealing applications. Compatible with butyl & asphalt flashing. Not Recommended For: Below waterline or below grade applications; joints exceeding 1/2" wide by 1/2" deep; window glazing. Features: Adheres to Wet Surfaces • Extreme Flexibility • Applies at Temperatures as Low as 20°F • Low Odor • Paintable • Low VOC • Cured Sealant is Mold & Mildew Resistant • Excellent UV Resistance Adheres To: Vinyl • Aluminum • Metal • Fiber Cement • Wood • Masonry • Most Common Building Materials</p> <p>SPECIFICATIONS: AAMA 803, Type I & AAMA 808, ASTM C920 Meets or Exceeds</p> <p>PHYSICAL PROPERTIES: VOC Content: CA ARB <3% wt./wt. (CCSC) Solids: 99.9% by weight Application Range: 20°F to 120°F Shelf Life: 12 months Skin Time: 45 minutes Cure Time: 24 hours</p> <p>Uncured Sealant Clean-Up: Mineral Spirits Cured Sealant Clean-Up: Cut or Scrape Will Not Freeze</p>
BENEFITS	
<ul style="list-style-type: none"> • Ideal as a window or door flange sealant • No shrinkage • Adheres to wet and damp surfaces 	